



MANUAL HYDRO TEST PUMP

WK-50 WK-50E WK-50STL

Product Profile :

- For precise and quick compression testing and leak testing on pipe work systems and containers in heating and sanitary installations and in boiler and vessel manufacturing.
- Constant pressure levels and reduction of leak-prone connections.
- Weather and cold-resistant steel container.
- Easy to operate, compact design and light weight.



Product Specifications

Model No.	WK-50	WK-50E	WK-50STL
Maximum Pressure	50bar, 276 psi, 5 mpa	50bar, 276 psi, 5 mpa	50bar, 276 psi, 5 mpa
Container Type	Metal Body	Metal Body	Stainless Steel
Hub Suction Capacity	40 ml/stroke	16 ml/stroke	40 ml/stroke
Tank Capacity	12 L	7 L	12 L
Outlet Connection	1/2 "	1/2 "	1/2 "
Testing Fluid	Water, Oil	Water, Oil	Water, Oil, Others
Maximum Temperature	120°F	120°F	120°F
Weight	8.2 KG	4.3 KG	8.2 KG
Dimensions (L*B*H)	520*180*300mm	440*220*270mm	520*180*300mm

ELECTRICAL HYDRO TEST PUMP EPUMP-40

Product Profile :

- For precise and quick compression testing and leak testing on pipe work systems and containers in heating and sanitary installations and in boiler and vessel manufacturing.
- Ideal for Hydro test and car washing. • Easy to transport with the unique top handle and light weight.
- Extremely easy to operate and precise measurement.

Product Specifications

Model No.	EPUMP-40
Maximum Pressure	40 bar. 580 psi. 4 Mpa
Input Voltage Req.	220V, 50Hz, 1P
Power	600 W
Rotating Speed	2800 R/Min
Flow Rate	8 Ltr/Min
Outlet Connection	1/2"
Testing Fluid	Water, Oil
Weight	14 kg
Dimensions (L*B*H)	365* 300* 300 MM



**INNOVATIVE
CANADIAN
TECHNOLOGY**
a step ahead.